



999.00 EUR
 incl. 19% VAT, plus [shipping](#)

- Intel® Apollo Lake N3350/N4200 Processor
- 1 * SO-DIMM Dual CH DDR3L up to 8GB
- 2 * USB3.0, 6 * RJ45, 1 * RS232(RJ45 TYPE)
- M/B Form Factor : Mini ITX (170x170mm)
- 1U FLEX POWER_200W

| | | | | | |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|-------------------------------------------------|------------------------------------------|--|
| MB Model | – JNF692G6-335 / JNF692G6-420 (Mini-ITX) – JNF692G6-335B1 / JNF692G6-420B1 (Mini-ITX/1 pair support Bypass LAN) | | | | |
| Part No | – HBJC153F692-335B – HBJC153F692-420B | | | | |
| | Bypass LAN | Expansion 4 ports LAN PCI-E Card | Bypass LAN+ Expansion 4 ports LAN PCI-E Card | 2 Pairs of Bypass LAN | |
| | – HBJC153F692B-335B – HBJC153F692B-420B | – HBJC153F692-33G4 – HBJC153F692-42G4 | – HBJC153F692B-33G4 – HBJC153F692B-42G4 | – HBJC153F692-33B4 – HBJC153F692-42B4 | |
| BIOS | – AMI 128MB SMT Flash ROM | | | | |
| CPU/Chipset | – INTEL® Apollo Lake N3350/N4200 Processor | | | | |
| Memory | – 1 * SO-DIMM slots DDR3L-1866MHz up to 8GB | | | | |
| Storage | – 1 * 2.5" SATA3 6Gb/s internal drive bay – 1 * Full-size mSATA/mini-PCI Express shared slot | | | | |
| Expansion | – 1 * Full size Mini-PCIE – 1 * SIM Card Slot | | | | |
| Network | – 6 * Intel i211AT Gigabit LAN – 1 * Full-size mini-PCIE slot (802.11 b/g/n + BT 4.0 installed in WIFI model) | | | | |
| Rear Panel I/O | – 1 * Power SWITCH – AC INPUT / 1U FLEX 200W Power build in | | | | |
| Front Panel I/O | – 6 * RJ45 – 2 * USB3.0 – 1 * RS232 (RJ45 TYPE) – 1 * PW LED, 1 * Alarm LED – 1 * HDMI (Not assembled when shipped, wire placed in the parts box) – 1 * GPIO (Not assembled when shipped, wire placed in the parts box) – 2 * COM (optional- RS232/422/485) Expansion 4 ports LAN PCI-E Card: HBJC153F692-33(42)G4 Expansion 2 pairs of Bypass LAN PCI-E Card: HBJC153F692-33(42)B4 | | | | |

| | |
|--------------|-----------------------------------------------------------------------------------------------------|
| Power Source | - 1U FLEX 200W Power build in - AC 90~240V input |
| Compliance | - CE, FCC, RoHS |
| Temperature | - Operating Temperature: 0 ~ 40° C - Storage Temperature: -10 ~ 70° C |
| Dimensions | - 430 (W) x 252 (D) x 44 (H) mm |
| Packing | - Net Weight: 4.2KG - Gross Weight: 5KG - Color Box dimension: 560 (W) * 400 (D) * 380 (H) mm |
| OS Support | - Windows 10, Linux |
| Warranty | - 2 Year limited warranty |